

## **Anti-Fuse** (Anti-Spread, No-Flow Primer)

### There are two types of anti-fuse:

- Solvent based
- Water based

This technique does not require resist and can be used both with steamable dyes or heat-fixed paints. The anti-fuse is applied directly to the entire fabric using a large brush or better still a foam brush. The color no longer fuses on the fabric after it has been treated with anti-fuse.

When the anti-fuse is dry, paint directly by freehand, taking care not to overload the paintbrushes with color, whether the paint is pure or diluted.

With this technique, the colors after fixing will be a little less bright. In addition, there will be a front side and a dimmer back side, since the Anti-fuse waterproofs the silk.

### Solvent based H Dupont 2M Anti-fuse

Available in 100, 250 or 1000ml : DU 074 0100 000 (100 ml)  
DU 074 0250 000 (250 ml) - DU 074 1000 000 (1000 ml)

Based on Essence F solvent, it is the most widely used anti-fuse. It can be applied both **to white or already painted fabric**. It does not affect the suppleness or shine of the fabric.

- Solvent-based product
- Use for H Dupont Classic, Alter Ego or Plumes & Fleurs colors
- Does not affect the suppleness or shine of the silk
- Apply on white or already painted silk
- Before painting, the anti-fuse is applied to the silk using a brush or sponge. It closes the pores of the silk and allows to work without resist.
- Wait for complete drying before painting



### Water-based H Dupont 1HO anti-fuse

Available both in 100 and 250ml : DU 073 0100 000 (100 ml)  
DU 073 0250 000 (250 ml)

Water-based, it is used like the previous one but **on UNPAINTED silk**. After fixing the silk, it leaves a certain stiffness to the fabric that is difficult to remove even in the wash.

Recommended for the production of paintings and lampshades.

- Water-based product
- After fixing the silk, it leaves a certain stiffness to the fabric which is difficult to remove, even after washing
- Therefore particularly suitable for paintings or lampshades
- Applies only to unpainted silk
- Use with H Dupont Classic, Alter Ego or Arasilk paints
- Before painting, the anti-fuse is applied to the silk using a brush or sponge. It closes the pores of the silk and ensures a work without need for resist
- Wait for complete drying before painting

